ART 34 AMDT

202 775 8396;

Feb-11-00 10:44AM; C'\MyFiles\23739pct\claims01.wpd.

PCT/US98/22372

ent By: Nath & Associates;

December 9, 1999

POTUL 98/22372

IPEA/US 09 DEC 1999

Claims:

The use of a composition in the preparation of a medicament for use in the treatment of pathogenic microorganisms in a live animal, the composition comprising an atomized electro-chemically activated, anion-containing aqueous solution.

- 2. A composition for the preparation of a medicament for the treatment of pathogenic micro-organisms in live animals, the composition comprising an atomized electro-chemically activated anion-containing aqueous solution.
- 3. A method of treating pathogenic micro-organisms in a live animal, the method comparising the step of fogging the animal with a dosage of a composition comprising an atomized electro-chemically activated Anion-containing solution.
- 4. A composition #s claimed in claim 2 wherein the anioncontaining aqueous solution is prepared by means of electrolysis of an aqueous solution of a salt.
- 5. A composition as claimed in claim 4 wherein the anioncontaining solution includes species selected from the group comprising: ClO; ClO-; HClO; OH-;  $HO_2$ -;  $H_2O_2$ ;  $O_3$ :  $S_2O_8^2$ -; and Cl<sub>2</sub>O<sub>6</sub><sup>2-</sup>.

-9-

AMENDED SHEET

FAX RECEIVED

FEB 1 1 2000

**GROUP 1600** 

02/11/00 FRI 11:42 [TX/RX NO 5077] 2009

202 775 8396;

Feb-11-00 10:44AM;

Page 10/13

C.\MyFiles\23739pct\claims01.wpd

.PCT/US98/22372

December 9, 1999

PCTNS 98/22372 IPEA/US 09 DEC 1999

6. A composition as claimed in claim 2 wherein the anion-containing solution is produced by an electro-chemical reactor, the electro-chemical reactor comprising a through flow, electro-chemical cell having two co-axial cylindrical electrodes with a co-axial diaphragm between the electrodes so as to separate an annular inter electrode space into a catalytic and an analytic chamber.

- 7. A composition as claimed in claim 2 wherein the anolyte solution has a redox potential of between +600mV and +800mV and a pH of between 6.5 and 7.5.
- 8. A method as claimed in claim 3 wherein the fogging process comprises the step of atomizing the solution into the atmosphere in a volume to be treated, forming droplets of between 5 and 100 micrometers.

add A

-10-

AMENDED SHEET

FAX RECEIVED

FEB 1 1 2000

02/11/00 FRI 11:42 [TX/RX NO 5077] 2010